

COPPOGOLD



GILLETTO
In colto e cemento

Coppogold is an exclusive model in the Tegolaia range, which integrates well into different urban and rural landscape settings. Shape and colour blend seamlessly into restoration work in historic city centres, but are used wherever elegance and observance of the Italian architectural tradition are of value.

Sizes cm:	42x33 cm
Requirements:	10 pcs/sqm
Weight:	4.75 kg
Box:	120 pcs
Colours:	52 musky clay 56 spring, 64 sphinx, 55 vintage, 57 historic, 63 florentine, 53 rural.

DESCRIPTION	COLOUR	SOLAR REFLECTANCE INDEX IN ACCORDANCE WITH ASTM STANDARD E1980 - 11(2019)		
		hc = 5W/(m2*K)	hc = 12W/(m2*K)	hc = 30W/(m2*K)
CoppoGold	Spring	24	24	24
CoppoGold	Sphinx	66	66	66
CoppoGold	Vintage	21	21	21
CoppoGold	Historic	20	20	20
CoppoGold	Florentine	44	44	45
CoppoGold	Rural	25	25	24
CoppoGold	Musky clay	n/a	n/a	n/a
n/a	data not available			

COPPOGOLD TECHNICAL FEATURES

Resistance to flexure*:	> 2000 N
Minimum slope:	31%
Minimum overlap:	7.5 cm
Pitch:	32.5-33 cm

*Evaluated according to sec. 5.6 of UNI EN 491



ITEM SPECIFICATIONS

The roof covering is to be constructed with Coppogold Tegolaia type Painted compound, Antiqued, Ceramic or Crystalline Cement Tiles, to be chosen by the Works Manager.

The roof must be constructed with all accessories, including special and complementary elements, to create a roof according to the provisions of the "Criteria for the design, execution and maintenance of roofing made of clay or concrete roof tiles" according to UNI 9460:2008. The tiles must guarantee performance criteria that meets the requirements of the UNI EN490 standard in accordance with UNI EN491.

The manufacturer must demonstrate that they have a quality management system in place, certified according to the UNI EN 9001:2015 standard, issued by an accredited body.



Gruppo Industriale TEGOLAIA
Via della Liberazione, 48 Casier (TV)

tel. 0422 6711

info@tegolaia.com
www.tegolaia.com

15/05/2023 Rev. 002